

Ref #	Hits	Search Query	DBs	Default Operator	Plurals	Time Stamp
L1	167751	light near source and optic\$4 and (sensor or infrared near detector or photodiode\$1 or visible near light or laser or infrared near transceiver or receiver)	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT	OR	OFF	2005/05/06 21:09
L2	99691	(object or vehicle or headlight ) and l1	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT	OR	OFF	2005/05/06 20:36
L4	23986	adjust\$3 with parameter	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT	OR	OFF	2005/05/06 21:16
L5	885	l2 and l4	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT	OR	OFF	2005/05/06 20:46
L6	130	(beam near pattern or beam near location or beam near focus or beam near angle) and l5	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT	OR	OFF	2005/05/06 21:21
L7	116	l6 and @ad<="20021212"	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT	OR	OFF	2005/05/06 20:57
L8	725	l5 and @ad<="20021212"	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT	OR	OFF	2005/05/06 21:07
L9	21	l8 and transceiver	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT	OR	OFF	2005/05/06 21:07
L10	7	l9 and vehicle	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT	OR	OFF	2005/05/06 21:09

L11	128	adjust\$3 with parameter and vehicle and l1	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT	OR	OFF	2005/05/06 21:06
L12	109	l11 and @ad<="20021212"	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT	OR	OFF	2005/05/06 21:09
L13	7	l12 and transceiver	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT	OR	OFF	2005/05/06 21:07
L14	1491	light near source and optic\$4 and (sensor or infrared near detector or photodiode\$1 or visible near light or laser ) and transceiver and receiver	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT	OR	OFF	2005/05/06 21:18
L15	258	l14 and vehicle	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT	OR	OFF	2005/05/06 21:09
L16	175	l15 and @ad<="20021212"	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT	OR	OFF	2005/05/06 21:22
L17	6	adjust\$3 with parameter and l16	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT	OR	OFF	2005/05/06 21:16
L18	1397	light near source and optic\$4 and (sensor or infrared near detector or photodiode\$1 or visible near light or laser ) and transceiver and receiver and control\$4	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT	OR	OFF	2005/05/06 21:18
L19	9	l18 and l6	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT	OR	OFF	2005/05/06 21:20
L20	13730	vehicle and light near source and optic\$4	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT	OR	OFF	2005/05/06 21:21

L21	878	(beam near pattern or beam near location or beam near focus or beam near angle) and I20	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT	OR	OFF	2005/05/06 21:22
L22	181	I21 and headlight	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT	OR	OFF	2005/05/06 21:22
L23	121	I22 and @ad<="20021212"	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT	OR	OFF	2005/05/06 21:22